STANDARD DEPARTURE ROUTES – INSTRUMENT (SID) FRANKFURT MAIN RWY 18 SIDs with Route Designator **TANGO** 

- 1. SIDs with designator **TANGO** (Contingency SIDs) will be assigned **by ATC only** under special circumstances, e.g. closure of one of the parallel runways when Landing Direction is 07.
- 2. NON-RNAV (enroute only) equipped aircraft shall use NON-RNAV SIDs with designator CHARLIE and QUEBEC respectively.

Designator	Route	After Take-Off		Remarks
		Climb to	Contact	нетакѕ
1	2	3	4	5
ВІВТІ 2Т	BIBTI TWO TANGO On RWY track to 800; on R356 RID to 6.4 DME RID north of RID (max. 220 KIAS); RT, on R199 FFM to 19.4 DME FFM; RT, (max. 250 KIAS during turn) on track 264° to PIPIX; RT, (max. 250 KIAS during turn) on track 283° to GISNO; RT, (max. 250 KIAS during turn) on track 318° to ULKIG(△); LT, on track 282° to OBOXO(△); RT, on track 073° to RUDUS(△); LT, on track 312° to MASIR; RT, on track 335° via RAVKI to DITAM; LT, on track 326° via OBOKA to BIBTI(△).  Cross 6.4 DME RID max. 4000. GPS/FMS RNAV: [A800+] - DF160[K220-; A4000-; R] - DF200[K250-; R] - PIPIX[K250-; R] - GISNO[K250-; R] - ULKIG[L] - OBOXO[R] - RUDUS[L] - MASIR[R] - RAVKI - DITAM[L] - OBOKA - BIBTI.	4000 ft	Langen Radar 136.125*	After 19.4 DME FFM BRNAV equipment necessary.
MARUN 2T	MARUN TWO TANGO On RWY track to 800; on R356 RID to 6.4 DME RID north of RID (max. 220 KIAS); RT, on R199 FFM to 19.4 DME FFM; RT, (max. 250 KIAS during turn) on track 264° to PIPIX( $\triangle$ ); RT, (max. 250 KIAS during turn) on track 283° to GISNO( $\triangle$ ); RT, (max. 250 KIAS during turn) on track 318° to ULKIG( $\triangle$ ); LT, on track 282° to OBOXO( $\triangle$ ); RT, on track 088° to WBD ( $\triangle$ ); RT, on track 088° to WBD ( $\triangle$ ); LT, on track 004° via ALIDI to MARUN ( $\triangle$ ). Cross 6.4 DME RID max. 4000. GPS/FMS RNAV: [A800+] - DF160[K220-; A4000-; R] - DF200[K250-; R] - PIPIX[K250-; R] - GISNO[K250-; R] - ULKIG[L] - OBOXO[R] - RUDUS[R] - WBD[L] - MABOB[L] - TESGA[L] - ALIDI - MARUN.			
TOBAK 4T	TOBAK FOUR TANGO On RWY track to 800; on R356 RID to 6.4 DME RID north of RID (max. 220 KIAS); RT, on R199 FFM to 19.4 DME FFM; RT, (max. 250 KIAS during turn) on track 264° to PIPIX(△); RT, (max. 250 KIAS during turn) on track 283° to GISNO(△); RT, (max. 250 KIAS during turn) on track 318° to ULKIG(△); LT, on track 282° to OBOXO(△); RT, on track 073° to RUDUS(△); RT, on track 088° to WBD (△); LT, on track 028° to MABOB; LT, on track 016° to TESGA; RT, on track 038° to TOBAK (△).  GPS/FMS RNAV: [A800+] - DF160[K220-; A4000; R] - DF200[K250-; R] - PIPIX[K250-; R] - GISNO[K250-; R] - ULKIG[L] - OBOXO[R] - RUDUS[R] - WBD[L] - MABOB[L] - TESGA[R] - TOBAK.			After 19.4 DME FFM BRNAV equipment necessary.     Not for flights continuing via Z10.

(Sample: OBOXO fly-over way point)

Contact LANGEN RADAR when advised by Tower!

<sup>\*</sup> Departure frequency may deviate from the frequency published. Check ATIS for current departure frequency.